
Three Really Useful Accessories



NATURAL CONTINUES OF THE STATE OF THE STATE


*) JAKARAN MANAKANAKANAKAN WANAKANAKAN

BASKET LAMP CLIP

No. 1095

Specially designed for easy removal, this sturdy clip can be used either on the front or rear of the basket. It can be used to hold a temporary rear light, sidecar lamp or inspection lamp.

Black Enamelled .. 1/-




BASKET LAMP BRACKET

No. 1095A

A spring steel clip that holds the lamp securely and well down on the basket.

Black Enamelled Spring Steel 9d.



CYCLE FEEDING BOTTLE CARRIER

No. 1294

(Regd. Design 824886)

Grips the bottle lightly and securely. Bottle can be taken out and replaced with one hand. Rattleproof.

2/6 each

HERBERT TERRY & SONS LIMITED REDDITCH, ENGLAND




O.H.V. SPRING COMPRESSOR.

endandandendendendendendendendendenden

TO THE TAXABLE PARTY OF THE PAR

COLUMN STATES OF THE STATES OF



No. 1124. Registered No. 735938.


This Compressor was specially designed to make the removal of O.H.V. Springs a simple job. The thread of the screw is deep and square cut, and the frame case hardened steel braced, to give rigidity. It will exert a pressure of 250 lbs.

For 250 c.c. .. 7/6 For 500 c.c. .. 8/6


TERRY'S MOTOR CYCLE SIDE VALVE SPRING LIFTER

is a very efficient tool for removing Side Valve Springs. The Ratchet locks the lever in position, leaving both hands free to extract the cotters.

1/6 each. 678B Strong, 2/-.




GUDGEON PIN REMOVER.




A thoroughly dependable tool. It will cover a range of pistons up to 80 m/m. and remove the most obstinate gudgeon pin. The screw has a deep square cut thread. Four stages of adjustment are provided on the band; four assorted diameter screw heads are also included, three being screwed into the tommy-bar when not in use.

Electro-galvanized finish - 4/6 each.

PISTON RING EASER.






This little hardened and tempered steel tool is a great help when removing obstinate piston rings. The tongue passes under the ring, which in turn passes through the slot; the tool is then easily pushed round the piston, leaving the ring free to be removed.

9d. each.

VALVE GRINDING TOOL.




CONTRACTOR DESCRIPTION OF THE PROPERTY OF THE

No. 1167

Grips the valve stem securely and enables the valve to be held firmly down on its seating. Made from blued steel in two sizes: to grip 5 in. and 3 in. valve stems.

1/- each.

AND THE PROPERTY OF THE TRANSPORT OF THE PROPERTY OF THE PROPE POCKET FEELER GAUGE.




Small enough to slip easily into the waistcoat pocket, this handy little gauge fills a long-felt want.

The six accurate blades are the most popular sizes, i.e., .003, .004, .006, .008, .010, .018.

When closed the blades fit snugly into the plated and polished handle.

No. 1175 . . 1/- each.

MAGNETO SPANNER. TAPPET SPANNERS.



No. 905

This little spanner is one of the most popular of the Terry range. It has eight sizes, a screwdriver and a feeler gauge.


1/6 each.



To prevent wear on the corners of the tappet a well-fitting spanner is essential. Terry Tappet Spanners have accurately milled jaws and while they are necessarily thin they are extremely tough.


No. 1083 Gaps .462 x .540 .. 1/6 pair. No. 1088A Gaps .610 x .720 .. 1/8 "

KICK-UP STAND CLIPS.



No. 687

A first quality, rapid-acting clip. The spring-loaded bolt gives extra tension. 1/3 each.



No. 1063

Positive lock type. Cannot be shaken loose by vibration. Black Enamelled . . 2/-

STEEL TYRE LEVERS.



No. 71

Hardened and tempered steel spoon-shaped Tyre Levers. Being pressed from the rod, these Levers have tremendous strength and have justly earned the title "Clubman's friend."

> Bronzed Finish .. 6d. pair.




No. 735

Spring steel Tyre Levers, tested to be the correct length to give the greatest leverage. All edges are rounded and smooth. Packed in sets of three-blued steel finish.

Cycle .. 6d. set.

Motor Cycle .. 1/- set.



edenie de la comparta del la comparta de la comparta del la comparta de la comparta del la comparta de la comparta de la comparta del la comparta d

LUCALITY OF THE STATE OF THE ST


TO TO THE TOTAL PROPERTY AND THE TOTAL PROPERTY OF THE TOTAL PROPE

No. 1176

The TERRY CYCLE STEP

Fits over the existing step, and gives a more comfortable and safer footing.


6d. each.



No. 677

Patent "Ironclad" Acetylene BURNER CLEANER.

(Registered No. 690,670/22.) Forty fine-gauge wires in coiled spring case. 2d. each.



POCKET SCREW DRIVER

No. 748


With four blades chromium plated and complete with pocket.

3d. each.

ADDITION OF THE PROPERTIES OF THE PROPERTIES OF THE PROPERTIES OF THE PROPERTIES.

MUNICIPAL SALVANIA SA


LAMP BRACKETS.



D-shaped Fork Bracket

with set screw, front or rear.

Enamelled . . 6d. each.



D-shaped Bracket

A to the a december of the second of the sec

CONTRACTOR OF THE STATE OF THE

CAMPANDALLA CONTRACTOR CONTRACTOR

CONTROL OF THE STANKING CONTROL OF THE STANKING OF THE STANKIN

front or rear.


Enamelled .. 9d. each.



No. 461

Spindle Fixing Bracket


Chromium Plated .. 6d. each. Enamelled 3d. "



No. 1218

Round Fork Bracket front or rear.


Enamelled .. 6d. each.



No. 1266

Extended Head Bracket

Chromium Plated .. 1/- each. Enamelled .. 9d. "




No. 463


Head Bracket

Chromium Plated .. 6d. each. Enamelled 3d.





No. 12
Wide Steel
Clip.
3d. pair.



No. 1123
Celluloid covered Band, in grey, black, brown, or white.

41d. pair.



No. 2 Narrow Steel Clip.

2d. pair.



No. 9
Narrow Steel Band.
3d. pair.




No. 1204
Celluloid Covered Clip, in black, brown, grey, 4½d. pair.



No. 4
Wide Steel Band.
3d. pair.

INFLATOR CLIPS




ROUTE CARD

No. 555 A

Holds map or route card in any position on the handlebar. Little sliding clips are adjustable to take any size card. Bronzed finish.

1/- each.




No. 1171

Convex-shaped bands make these Clips grip with great strength. The slots and threads of the screws are deeply cut. One Clip is sprung, the other solid.

Black Enamelled, 6d. pair.

REX PATTERN INFLATOR CLIP



No. 692


Well made Clip in blued steel. The jaws are lined to prevent scratching. Obtainable in sizes suitable for cycle and motor cycle.

Motor Cycle ... $8\frac{1}{2}d$, pair. Cycle ... $7\frac{1}{2}d$.

(F) YM

A SUPER ROADSTER SADDLE

WITH ADJUSTABLE SEAT AND REAR SPRINGS




AND ENGLISHED BE CONTINUED OF THE CONTINUE OF

LALLAND WALLEN WALLEN WALLEN WALLEN

This illustration not only shows the perfect network of springs of the Terry Saddle, but the two new exclusive features which make it the World's Best:—

- (1) Notice the Rear Springs. They can be used two, three or four alternately, just to suit your need.
- (2) The Seat Springs too, can be slackened or tightened by the turn of a screw in the nose.


These two patented ideas are fitted only on Terry Saddles.



| No. 1263 | Gents Roadster Model; 103"> | < g"; | |
|------------|-----------------------------------|--------|------|
| | weight 2 lbs. 122 ozs. | | 13/6 |
| No. 1264 | Ladies Roadster Model; 9"× | 83"; | 11.6 |
| | weight 2 lbs. $6\frac{1}{2}$ ozs. | | 13/6 |
| Replacemen | nt Top for Adjustable Roadster | Model | 4/6 |
| New Pat | ent Numbers: 457,373, 454,892 | 455,16 | i9. |


A PERFECT CLUB SADDLE

WITH ADJUSTABLE SEAT SPRINGS AND A
PATENTED HINGED FRAME



APPERENTIAL BEGING OF THE STANDARD OF THE STANDARD STANDED TO BE SEED TO STANDARD ST

The skeleton illustration shows the two features which make this saddle ideal for all club riders. By twisting a screw in the nose the seat springs can be tightened or slackened as you desire. Different tension can be used to suit varying roads. The patented hinged frame takes the shock of sudden jars and prevents spinal fatigue.




No. 1265 Club Model, Ladies or Gents; $11'' \times 7\frac{1}{2}''$; weight 2 lbs. .. 10/6

Replacement Top for Adjustable Club Saddle, 4/6
New Patent Numbers: 457,373, 454,892, 455,169.

HAVE

IN THE LONG RUN ON A
TERRY SPRING SEAT SADDLE




and the design and the selection of the

RACING MODEL

as used by "Oppy," the famous Australian cyclist. After his record-breaking ride to Bath and back he said "Although I have been in the saddle over ten hours it is the most comfortable saddle I have ever ridden."


| No. | 1238R | with Rexine Top; $10\frac{3}{4}" \times 5"$; weight, 1 lb. 11 ozs. | ex = | 9/6 |
|-----|-------|--|------|------|
| No. | 1238 | with Leather Top; $10\frac{3}{4}" \times 5"$; weight, r lb. 11 ozs. | • • | 11/6 |
| | Rep | lacement Top for above Saddle: Rexine 4/6; Leather | 6/6. | |




CLUB MODEL

Designed specially for the club rider who wants a seat more comfortable than a sprint saddle. It is hard enough to give the necessary resistance, yet it affords the comfort that only springs can give. No saddle soreness — no fatigue — if you ride on a "Terry."

No. 1198 Rexine covered, Ladies or Gents; 11"×7½"; weight 1 lb. 15 ozs. 8/6
Replacement Top for Club Saddle, 4/6.



The Proof of the Saddle is in the Seating




THE THE TAXABLE TO TH

ATTRACTOR OF THE STANDARD STAN

ROADSTER MODEL

The most popular spring seat saddle. Nineteen tempered springs make it a hammock of perfect ease. Designed for the rider who desires comfort on his rides, it makes the casual cyclist an enthusiast.

No. 1086 Gents Roadster Model with Rexine Top: 104"×9"; weight 2 lb. 13 ozs. 11/6
No. 1087 Ladies Roadster Model with Rexine Top; 9"×84"; weight 2 lb. 7 ozs. 11/6
Replacement Top for Roadster Model, 4/6.




OVERSEAS MODEL

Designed specially for use abroad where the roads are very bad. It is built on robust lines: the undercarriage is girder steel, the springs are heavier gauge, the seating area is $11\frac{1}{2}'' \times 10\frac{1}{2}''$; it is an ideal saddle for extra heavy riders.

No. L1042 Gents Overseas Model, Rexine Top; $11\frac{1}{2}" \times 10\frac{1}{2}"$; weight 4 lbs. 5 ozs. 14/6 No. L1042L Ladies Overseas Model, Rexine Top; $10\frac{1}{2}" \times 9\frac{1}{4}"$; weight, 3 lbs. 7 ozs. 14/6 Replacement Top for Overseas Model, 5/6.

TERRY' Jes To Vintering




LUKUKUKUKAN KAKKIKAKI KAN KAN KAN KAN

CLUB TOURIST MODEL

Built on the same graceful lines as the "Club" but with a larger seating area. It is a popular model and fitted as standard on many famous cycles. Perfectly supple from end to end, it has no hard spots. It simply adjusts itself to your every movement, giving you comfort that encourages you to ride and ride.

| No. | 1199 | Gents Club Tourist, Rexine Top; 103"×81"; weight, 1 lb. 15 ozs. | 8/6 |
|-----|-------|---|---------|
| No. | 1199L | Ladies Club Tourist, Rexine Top; $9\frac{3}{4}" \times 8\frac{1}{2}"$; weight, 1 lb. 15 ozs. | 8/6 |
| | | Replacement Top for Tourist Model, 4/6. | |




C.T.C. MODEL

A speed model with the added comfort of a sprung undercarriage pivoting from the nose and supported in the rear with two flexible springs. The extreme comfort of this model will smooth the roughest roads and insulate the rider from all hurtful vibration.

| No. 1088 | Gents C.T.C. Model, Rexine Top; 11" × 7½"; weight, 2 lb. 11 ozs. | 10/6 |
|-----------|--|----------|
| No. 1088L | Ladies C.T.C. Model, Rexine Top; 10" × 7½"; weight, 2 lb. 6 ozs. | 10/6 |
| | Replacement Top for C.T.C. Model, 4/6. | 1950000 |

SPARE PARTS FOR TERRY SADDLES



To order seat springs for any saddle, count from outside to centre, as illustrated. Give overall length and type of ends of each spring. To make the ordering of parts easier, each saddle has its list number stamped on the inside of the girder frame.

SEAT SPRINGS

For Numbers 1198 and 1238, 2/- dozen Nose; 1/6 dozen Rear.
For numbers 1086, 1088 and 1199, 1/6 dozen Nose; 2/- dozen Rear.
For number 1042, 2/6 dozen Nose; 3/6 dozen Rear.




Rexine
Saddle Tops
for all Models.
4/6 each.

THE FOLL THE BUILDING TO THE TRANSPORT OF THE PROPERTY OF THE PROPERTY OF THE FOLL OF THE FOLL OF THE PARTY.

SERVENCE BELLEVILLE STATE STATE STATES STATE

Cranked Undercarriage Spring for Nos. 1086, 1087, and 1088. 9d. each.



CONTRACTOR CONTRACTOR


annual designation of the state of the state



Straight Undercarriage Spring for Nos. 1086, 1087, and 1088. 9d. each.

TALLER WALLEN WITH THE WALLEN WALLEN


MOTOR CYCLE SADDLES



THE DOMINION

A motor cycle saddle of astounding comfort. The deep bucket seat envelops the rider in ease and gives an added feeling of security as slipping off the back is almost impossible. A saddle to be proud of. Specify one on your new machine.

No. 1138 $17\frac{1}{2}$ " × 14"; weight, 7 lbs. 10 ozs. . . 42/-



STANDARD MODEL

This is the pioneer model that achieved fame for the name of "Terry" among motor cyclists. In its various forms, designed to suit different makes of machines, it has been standardised for many years, either with seat pillar or 3-point suspension attachments.

No. 1089/2 Seating area, $13\frac{1}{2} \times 14$ in... ... 30/- each

No. 1089/1 Also supplied with a larger seating area of $13\frac{1}{2} \times 15\frac{1}{4}$ in. 32/6

TERRY'S PRIMUS STOVE CLIP.

This handy little Carrier clips on the stove and does not interfere with its use. It is Cadmium plated and therefore rust-proof.


The stove can be carried on the top tube against the head or underneath the saddle.

Suitable for Nos. **210** and **96** stoves.

No. **1270**. **9d**. each.

TENNIS RACKET CARRIER.

Leaves your hands free in any emergency — Cycle in safety! **THE GLIP** fixes to the front fork blade by means of a bolt and nut. A baize-lined automatic grip holds the racket. It cannot fall out, rattle, get scratched, or inter-



The Clip will carry a walking stick, umbrella

distortion.

stick, umbrella, camera tripod, fishing rod, or hockey stick.

fere with the


steering, and no

strains are put

upon it to cause

Black Enamelled, 2/- each.


WATCH HOLDER



For fixing the watch in a visible and safe position on the cycle handlebars. Chromium plated.

1/- each.

CAPE HOLDER



No. 1186.

Clips on to the seat pillar stem under the saddle and safely carries oilskins, bathing costume, spare tyre, etc. Although it grips tightly it can be easily opened. Weighs only 2 ozs.; made from tested steel rustproof wire.

1/- each.

